



# Wi-Fi 5 Cloud-Managed Wave 2 Wall-Plate Access Point

Provides in-demand speeds for in-room wired and wireless connectivity

## Product Highlights

EnGenius Cloud Managed ECW115 11ac Wave 2 2x2:2 Wall Plate Access Point with built-in 2-port Gigabit switch offers in-demand, high-speed in-room wired and wireless connectivity that is flexible and reliable. Deploy in hotel guest rooms, dorms, classrooms, and multi-tenant dwellings.



## Features & Benefits

- Dual-radio 2x2 802.11ac/a/b/g/n with MU-MIMO & Beamforming technology
- Supports up-to 867 Mbps in 5-GHz band & 400 Mbps in 2.4-GHz band
- Sleek, Low Profile Design for In-Room Wi-Fi & Wired Connectivity
- On-Board 2-Port Switch Offers Port-Based 802.1Q VLAN Support
- Connect & Power VoIP or other PSE devices on LAN1 & LAN2
- Cloud Manage unlimited number of AP's from Anywhere with the EnGenius Cloud App

## Standards

IEEE 802.11b/g/n on 2.4 GHz

IEEE 802.11a/n/ac Wave 2 on 5 GHz

## Antenna

2 x 2.4 GHz: 4 dBi

2 x 5 GHz: 5 dBi

Integrated Omni-Directional Antenna

## LED Indicators

1 x Power

1 x Cloud Connecting

1 x Multi-Color LED

## Physical Interface

1 x 10/100/1000 BASE-T, RJ-45 Ethernet Uplink Port (back plate)

2 x 10/100/1000 BASE-T, RJ-45 Ethernet Switched Ports (client ports)

Port 1 (PSE) 802.3af PoE (requires 802.3at power source)

1 x DC Jack

1 x Reset Button

## Power Source

Power-over-Ethernet: 802.3at Input

IEEE 802.11e Compliant Source

12VDC /1A Power Adapter

## Maximum Power Consumption

12W

## Wireless & Radio Specifications Operating Frequency

Dual-Radio Concurrent 2.4 GHz & 5 GHz

## Operation Modes

Manage Mode: AP, AP Mesh

## Frequency Radio

2.4 GHz: 2400 MHz ~ 2472 MHz

5 GHz: 5150 MHz ~ 5250 MHz, 5250 MHz ~ 5350 MHz, 5470 MHz ~ 5725 MHz, 5725 MHz ~ 5850 MHz

### Transmit Power

Up to 17 dBm on 2.4 GHz

Up to 17 dBm on 5 GHz

### Tx Beamforming (TxBF)

#### Radio Chains/Spatial Stream

2x2:2

### SU-MIMO

Two (2) spatial streams Single User SU-MIMO for up to 400 Mbps wireless data rate with VHT40 bandwidth to a 2x2 wireless client device under the 2.4GHz radio. Two (2) spatial stream Single User SU-MIMO for up to 867 Mbps wireless data rate with VHT80 to a 2x2 wireless device under the 5GHz radio.

### MU-MIMO

Two (2) Spatial Streams MU-MIMO up to 867 Mbps wireless data rate for transmitting to two (2) streams MU-MIMO capable wireless devices under 5GHz simultaneously.

### Supported Data Rates (Mbps):

2.4 GHz: Max 400

5 GHz: Max 867

802.11b: 1, 2, 5.5, 11

802.11a/g: 6, 9, 12, 18, 36, 48, 54

802.11n: 6.5 to 300 Mbps (MCS0 to MCS15) (Additional 25% bandwidth when enabling 256-QAM under HT40)

802.11ac: 6.5 to 867 Mbps (MCS0 to MCS9, NSS = 1 to 2)

### Supported Radio Technologies

802.11b: Direct-Sequence Spread Spectrum (DSSS)

802.11a/g/n/ac: Orthogonal Frequency-Division Multiplexing (OFDM)

802.11n/ac: 2x2 MIMO with 2 Streams

### Channelization

802.11ac Supports Very High Throughput (VHT)—VHT 20/40/80 MHz

802.11n Supports High Throughput (HT)—HT 20/40 MHz

802.11n Supports Very High Throughput (VHT) Under the 2.4 GHz Radio—VHT 40 MHz (256-QAM)

802.11n/ac Packet Aggregation: AMPDU, ASPDU

### Supported Modulation

802.11b: BPSK, QPSK, CCK

802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM

802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM

### Multiple BSSID

8 SSIDs on both 2.4GHz and 5GHz radios.

### VLAN Tagging

Supports 802.1q SSID-to-VLAN Tagging

Cross-Band VLAN Pass-Through

Management VLAN

### Spanning Tree

Supports 802.1d Spanning Tree Protocol

### QoS (Quality of Service)

Compliant With IEEE 802.11e Standard

WMM

### SNMP

v1, v2c, v3

### MIB

I/II, Private MIB

### Wireless Security

OWE

WPA2 Personal

WPA3 Personal (SAE) - WPA3 Only

WPA3/WPA2 Personal Mixed

WPA2 Enterprise

WPA3 Enterprise Suite B

Hide SSID in Beacons

MAC Address Filtering, Up to 32 MACs per SSID

Wireless STA (Client) Connected List

SSH Tunnel

Client Isolation

### Environment & Physical Temperature Range

Operating: 32°F~104°F (0 °C~40 °C)

Storage: -40 °F~176 °F (-40 °C~80 °C)

### Humidity (non-condensing)

Operating: 90% or less

Storage: 90% or less

### Dimensions & Weight

Weight: .80 lbs. (.363 Kg)

Length: 3.5" (90 mm)

Width: 5.5" (140 mm)

Height: 1.6" (40 mm)

### Package Contents

1 - ECW115 Cloud Managed Indoor Access Point

1 - Ceiling and Wall Mount Screw Kits

2 - Junction-plates (tall/short)

1 - Quick Installation Guide

### Warranty





2 Year

### Certifications

CE

FCC

IC




## ECW115 Indoor Access Point

Power LED



Gigabit Ethernet Port (PoE)



Reset Button

Power connector

Port 1 - Gigabit Port (PoE+) Uplink

Port 2 - Gigabit Switch Port with PoE Support

Plug & Play with Zero Configuration

# Scan & Go



EnGenius Technologies | 1580 Scenic Ave. Costa Mesa, CA 92626

Email: [partners@engeniustech.com](mailto:partners@engeniustech.com) | Website: [engeniustech.com](http://engeniustech.com)

Version: 1.00 07/2021

Features and specifications subject to change without notice. Trademarks and registered trademarks are the property of their respective owners. For United States of America: Copyright ©2021 EnGenius Technologies, Inc. All rights reserved. Maximum data rates are based on IEEE 802.11 standards. Actual throughput and range may vary depending on distance between devices or traffic and bandwidth load in the network.